



Technical specification – e-Inverter

Note: The specifications are subject to change without notices.

28321-03 /28320-03 e-Inverter 2000 • 28331-03/28330-03 e-Inverter 3000		
Product	e-Inverter 2000	e-Inverter 3000
AC Output Power	2000W	3000W
AC Output Peak Power	4000W	6000W
AC Output Current	8.7A	13.0A
Voltage	230VAC/50Hz	230VAC/50Hz
Waveform	True Sinewave (<3% TDH)	True Sinewave (<3% TDH)
Peak efficiency	90%	90%
AC Output socket	1x EU (Schuko) / UK (Type G)	2x EU (Schuko) / UK (Type G)
DC Input Voltage (Nominal)	12.5V	12.5V
DC Input Operating range	10.5–15.5Vdc	10.5–15.5Vdc
AC Input	N/A	13A
AC Input socket	N/A	IEC C13
AC Transfer Time	N/A	< 30 ms Transfer Relay Rating 16A (resistive load)
LED indicator	Status	Status
Input undervoltage	10.5V	10.5V
Input overvoltage	15.5V	15.5V
Certifications	R10, CE UKCA	R10, CE UKCA
Weight	10.6 kg	11.45 kg
Dimension (mm)	320x477x140	320x477x140
Warrenty	3 year	3 year
IP Rating	IP22	IP22